

We proudly present... CeNit® Strip Curtain




Fig. 1: Strip curtain Type SE



Fig. 2: Strip curtain Type EH

Product description	
Areas of application	<ul style="list-style-type: none"> › Car washes, convenience stores, hospitals, train stations, airports and more › Meat-& food processing companies › Cold storage & refrigerated vehicles › Warehouses, commercial & industrial companies › Public buildings
Technical Properties / Advantages	
Type SE (swivel mounted): Mounted on a support tube by means of galvanized clamps/ blue plastic clamps	✓
Type EH (hook-in-system): Mounted on a fastening rail by means of retaining clips	✓
Closure of openings by lamellar-like assembly of PVC strips	✓
Steel parts galvanized or made of stainless steel	✓
Temperature resistant from -20 °C to +60 °C	✓
Available either fully pre-assembled or as a modular system	✓
Tool-free unhooking & replacement possible (Type EH)	✓
Translucent	✓
Laterally rounded edges → Injury prevention	✓



We proudly present... CeNit® Strip Curtain

Overlap key strip curtain Type SE (swivel mounted)						
Type	Width of strip in mm	Thickness of strip in mm	Overlap		Definition of Type*	
			in mm	in %	Interior doors up to height in mm	Exterior doors up to height in mm
SE 2/8	200	2 (default) 3, 4 or 5	80	80	2,000	2,000
SE 3/6	300	3 (default) 2, 4 or 5	90	60	2,500	2,100
SE 3/8			120	80	3,200	2,500
SE 3/10			150	100	4,000	3,200
SE 4/6	400	4 (default) 2, 3 or 5	120	60	5,000	3,500
SE 4/8			160	80	6,000	4,500
SE 4/10			200	100	> 6,000	> 6,000

*Standard value

Overlap key strip curtain Type EH (hook-in system)						
Type	Width of strip in mm	Thickness of strip in mm	Overlap		Definition of Type*	
			in mm	in %	Interior doors up to height in mm	Exterior doors up to height in mm
EH 2/0	200	2 (default) 3 or 4	0	0	1,500	1,500
EH 2/35			35	35	1,700	1,700
EH 2/75			75	75	2,000	2,000
EH 3/09	300	3 (default) 2 or 4	14	9	2,100	2,000
EH 3/36			54	36	2,300	2,000
EH 3/63			94	63	2,500	2,100
EH 3/90			134	90	3,500	3,200
EH 4/17	400	4 (default) 2 or 3	34	17	3,500	2,700
EH 4/37			74	37	3,500	3,000
EH 4/57			114	57	3,500	3,500
EH 4/77			154	77	3,500	3,500
EH 4/97			194	97	3,500	3,500

*Standard value

